



# Tysso POStation 7000

## All-in-One Touch Screen POS Terminal

### 3 year manufacturers warranty

**Tysso POStation 7000 is an all-in-one point of service terminal developed to withstand the rigours of modern hospitality, retail and fashion environments. The POStation 7000 terminal, while increasing efficiency, accuracy, and flexibility, which are key features to the success of modern business, benefits both sellers and buyers. It increases sales, brings profits at an affordable price, is extremely reliable, of high quality and has excellent performance.**

The versatile I/O ports allow integration to a wide variety of POS peripherals, such as bar code scanners, receipt and kitchen printers, data collectors and cash drawers. The POStation 7000 terminal supports diversified applications with the choice of MSR, I-Button, dual 12" customer display or VFD customer display and wall mount options. Its cable management solution not only enables easy routing but also provides an elegant impression to the customers. The robust structure with aluminium die cast base and screen water spill proof features makes it capable to withstand daily usage under harsh operating environments.

The POStation 7000 is compatible with Windows 95/98/2000/XP and almost all Linux Distros w/2.6+ kernels. The embedded processor is 2.00 GHz as standard and with 512MB ram as standard provides high performance and reliability of the system with low power consumption. The easy access compact flash and HDD makes it a very serviceable terminal.

The POStation 7000 series satisfies strict market demands and ensures the competitiveness of your business that provides an excellent return on investment.



with second display



with customer display



wide range tilting angle



wall mount



### Features

- High performance processing-2.0GHz, 512MB Ram standard (Up to 3.2 GHz CPU,1 GB RAM)
- Water spill proof
- Steady aluminium die cast base
- Versatile I/O ports
- Tilting touch screen 0-80 degrees
- Easy access HDD and compact flash
- Elegant cable management
- Dual 12.1" display or VFD customer display options
- Wall mount option
- MSR card reader/I-Button options
- 802.11 WLAN function by mini PCI card option

For further details contact International POS on **01524 388811** or email **sales@iposltd.com**

International POS Ltd, Cameron House, White Cross, South Road, Lancaster LA1 4XF  
Telephone +44(0)1524 388811. Email: sales@iposltd.com

All specifications are subject to change without notice. All product names and company names used are for identification purposes only and may be trademarks of their respective owners.



# POStation 7000

## Specifications



### Main Board

CPU	P4 / Celeron 2.0GHz up to 3.2 Ghz.
Core Logic	Intel 852GM + ICH4
System Memory	SODIMM, DDR266/333, 256MB up to 1GB
OS Support	Win2000, NT, Win XP, Embedded XP(XPe), WinCE, WEPOS, Windows Vista (Basic), Linux: Ubuntu 6.06, 7.04, FC4/5/6/7, Novell Open Suse 10

### Display

TFT LCD	15-Inch
Brightness	250 nits
Resolution	1024 x 768 Pixel
Touch Screen	5Wire Resistive Type
Tilting Angle	0 - 80 Degree

### Storage Device

HDD	1 x EIDE 2.5" Type
Compact Flash	1 x Slot Type II, Non-removable

### I/O Ports

Serial	6 x RS-232 COM 3 / 4 / 5 / 6: DB-9, male (Pin 9 RI or 5V or 12V Selectable) COM 1 / 2: Internal for I Button and MSR
Parallel	1 x DB-25, female, supports EPP/ECP
USB	4 x USB 2.0 External 1 x USB 2.0 Internal for Touch Control BD 1 x USB 2.0 Internal Reserved
PS/2 Mouse	1 x 6-pin mini DIN
PS/2 Keyboard	1 x 6-pin mini DIN
LAN	1 x RJ45, 10/100 Base-T, supports wake on LAN
VGA	1 x DB-15, female
DC Jack	1 x 12VDC Output for 2nd Display
Cash Drawer	1 x RJ11, 12VDC
Audio Jack	1 x Mic In, 1 x Audio Out
Expansion	1 x Mini PCI



with second display



with customer display



wide range tilting angle



wall mount

### Others

Power Input	External Adapter 12VDC 150W
Color	Black
Compliance	FCC / CE / WEEE / RoHS
Weight Include Packaging	10 Kgs
Dimension (W x D x H)	367 x 335 x 356 mm
Operating Temperature	5 C ~ 35 C
Storage Temperature	-20 C ~ 60 C
Storage Humidity	20% - 80% RH, non-condensing

### Optional Accessories

Second Monitor	15-inch, 12.1-inch, or 10.4-inch TFT/LCD Display
Customer Display	VFD panel with Pole, 20 x 2 characters, RS232 Interface
Magstripe Card Reader	Triple Track (track 1, 2, and 3) PS/2 or RS-232 interface
i-Button	Dallas Key, RS-232 Interface
Wall Mount Bracket	VESA Bracket Kits

For further details contact International POS on **01524 388811** or email **sales@iposltd.com**

International POS Ltd, Cameron House, White Cross, South Road, Lancaster LA1 4XF  
Telephone +44(0)1524 388811. Email: sales@iposltd.com

All specifications are subject to change without notice. All product names and company names used are for identification purposes only and may be trademarks of their respective owners.